



DEWERT

A DewertOkin Technology Brand

Medical.

The inner strength.



Accucontrol Eco 2.5 attached to the JLDQ.29M

ACCUCONTROL ECO 2.5

The Accucontrol Eco 2.5 control unit redefines efficiency and user-friendliness for mobile applications in the hospital and care sector.

Thanks to the swivel bracket attached directly to the drive and the integrated buttons, there is no need for an external handset, which is not only cost-efficient but also minimizes installation costs. The integrated buttons are always within easy reach and enable effortless operation. The control unit also has soft start, which ensures particularly gentle and controlled movement of the drive.

Thanks to the powerful lithium-ion battery with the lowest possible self-discharge, the Accucontrol Eco 2.5 guarantees a reliable and mains-independent power supply for everyday use.

As a system supplier, we offer the control unit including drive and swivel bracket. Optionally, you can add other specific components as required, including a quick charger, an external handset, a control unit for two motors (e.g. for the base-width adjustment motor of a patient lift) and much more.

CUSTOMER BENEFITS:

- **Integrated and flexible operation:** Effortless operation thanks to integrated buttons and swivel mount
- **Reliable power supply:** Powerful lithium-ion battery with the lowest possible self-discharge rate
- **Low installation effort:** No need for an external handset and cable routing, as well as simple installation
- **System supplier:** Everything from a single source, maximum efficiency and coordination
- **Flexible extensions:** Optional additional components according to individual requirements



Application example on the patient lift



DEWERT

A DewertOkin Technology Brand

Medical.

The inner strength.

TECHNICAL DATA

Length	212 mm
Height	93 mm (emergency stop button included)
Width	130 mm
Weight	730 g
Rechargeable battery capacity	2.5 Ah
Rechargeable battery nominal voltage	25.2 V
Operational temperature range	+5 - +40 °C

TECHNICAL DRAWING

